

OPTIONS

WALL- AND CEILING-PANELS

- PLASTISOL steelplate
White protective film - white 9002 (RAL) - 0,73 mm
- ALU-ZINC steelplate (min. quantity 100 m²)
alu-zinc coating 185 grs./m² - thickness 0,50 mm without protection film
- STAINLESS STEEL FACING - 0,60 MM - with protection film
Standard facing:
 - . Aisi 316 - pinpoint finish
 - . Aisi 304 - line-brushedFinishing at request:
 - . Aisi 316 - line-brushed
- LOCKING-SYSTEMS, every 300 mm

FLOORPANELS

- PVC COATING (S) grey - steelplate - 1 mm - with protective film
not suitable for trolleys
- MARINE PLYWOOD (WBP) - 9 mm
without any facing
- FACINGS TO BE USED ON MARINE PLYWOOD (cut to sizes, but not pré-drilled)
 - * ALUMINIUM PLATE, with non-slip (Dámier Quintett)
 - 2,5/4 mm - raised pattern = 750 kg - charge on 4 rubberized wheels
 - 3,5/5 mm - raised pattern = 1000 kg - charge on 4 rubberized wheels
 - * ALUMINIUM PLATE smooth
 - 3 mm - 750 kg - charge on 4 rubberized wheels
 - * Galvanized STEELPLATE
 - 3 mm - 1200 kg - max charge on 4 rubberized wheels
 - * One-side METALLIZED STEELPLATE - rhombus-checked
 - 5/7 mm - 1500 kg - max charge on 4 rubberized wheels
- STAINLESS STEELPLATE 0,80 mm (AISI-304),
pattern 5 WL, antislip R13, on marine-plywoodcovered panel
max charge on 4 rubberized wheels 500 kg

PARTITION WALLS

- PARTITION WALL WITH "T" panel
 - * jointing profile for wall- and ceiling-panels
 - * jointing profile for floor-panels
 - ISO 6 = "U"-profil with screws
 - ISO 8, 10 en 14 = 2 positioning profiles with screws
- INTERIOR CORNER-PROFILE
60 x 60 mm - white lacquered - 9002 (RAL) with screws
Only available in length of 3000 mm of one piece

CORNER-PROFILES FOR ANNEX ROOMS

- ISO 6 ANNEX-CORNER-PROFILE - one side faced with white lacquered steelplate
with fastening screws
- ISO 8 ANNEX-CORNER-PROFILE - one side faced with white lacquered steelplate
with fastening screws
- ISO 10 ANNEX-CORNER-PROFILE - one side faced with white lacquered steelplate
with fastening screws

INSULATION

- PANEL M1 (Classification reaction to fire : B2)

ISO 14 ROOMS WITHOUT FLOOR

- On ALU-ZINC "U"-shaped floorprofile (30x200mm) - 1 mm thick with plugs.

FINISHING PROFILES

